





UP to 371°C



HS CODE
63079098
CARTON SIZE / PCS.
60 x 40 x 24 cm / 12
AET N°2777/10962-01/E01-01
<b>Satra Technology Europe Ltd., N° 2777,</b> Bracetown Business Park, Clonee, Dublin, D15YN2P, Ireland
MODULE D FI14/14003.02
<b>SGS Fimko Oy, N°0598</b> Takomotie 8, 00380 HELSINKI, Finland
AET (UKCA) N°AB0321/16021-01/E01-01
<b>Satra Technology Centre, N°0321</b> Wyndham Way, Telford Way, Kettering Northamptonshire, NN16 8SD, United Kingdom
MODULE D 11 IN14/14003
<b>SGS United Kingdom Ltd., N°0120</b> Unit 202B, Worle Parkway, Weston-super-Mare, BS22 6WA, United Kingdom



REF.	FA 30 402 10	FA 30 402 15
LG.  KG	1.0 m (connectors included)	1.5 m (connectors included)
CE	EN 355:2002, ISO 9150, ISO 15025	
MAT.	45 mm ARAMID	
	45 mm	
	NO	
+	PPE-R 11.063	
	1.6 KG	1.87 KG



**Largeur de l'absorbeur d'énergie**  
 Width of the energy absorber  
**Ancho del absorbedor de energía**  
 Larghezza del assorbitore di energia  
**Breite des Falldämpfers**



**Longueur** Poids maxi utilisateur  
**Length** Max. user weight  
**Longitud** Peso máximo del usuario  
**Lunghezza** Peso Max. dell'utente  
**Länge** Höchstgewicht des Benutzers



**Matière connecteur haut / connecteur bas**  
 Material of top connector / bottom connector  
**Material conector alto / conector bajo**  
 Materiale connettore alto / connettore basso  
**Material oberes / unteres Verbindungselement**

+

**Point fort**  
 Key feature  
**Ventaja principal**  
 Punti forti  
**Produktvorteil**



**Homologué pour le travail à proximité d'arêtes vives**  
 Approved for work near sharp edges  
**Homologado para trabajo cerca de aristas vivas**  
 Omologato per lavoro in prossimità di spigoli vivi  
**Zugelassen für Arbeiten in der Nähe scharfer Kanten**